

GRAIN PILE PICKUP >
SUPER SCOOP

Load a waiting 1,000 bushel trailer in 6 minutes with the 11,000 BPH Super Scoop.
Available in standard or center feed models. Easy to mount and dismount.
Fits most tractors 90 HP and up. Attach a hydraulic spout for more efficient and precise loading.



Sudenga®
INDUSTRIES, INC.



WWW.SUDENGA.COM

- Easy to mount and dismount
- 35' and 40' inclined conveyor (center feed and standard scoop)
 - Heavy duty throughout
- Load a waiting 1,000 bushel trailer in under 6 minutes
 - 11,000 BPH
 - 16" diameter intake auger

Learn more
or get a quote



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com

MADE
★IN THE★
USA

GRAIN PILE PICKUP >
SUPER SCOOP



Piles of grain to pick up? Sudenga has the solution.

Load a waiting 1,000 bushel trailer in 6 minutes with the 11,000 BPH Super Scoop. Available in standard or center feed models. Easy to mount and dismount. Fits most tractors 90 HP and up. Attach a hydraulic spout for more efficient and precise loading.

SUPER SCOOP
 BY **Sudenga**
INDUSTRIES, INC.

SPECIFICATIONS

Scoop Blade	3/16" blade thickness; 10' wide on standard models; 8' wide on center feed models; 16" helicoid flighting (5/16" thick) on 4" pipe (1/4" wall); Double #80 roller chain; pillow block bearings; 122 RPM flight speed; attachment arms for Category III 3-point
Inclined Conveyor	10 ga. abrasion resistant steel lower trunking and pan; 1" flame cut sprockets on 2 7/16" top and bottom shafts; 42,000# tensile strength chain; 1/2" UHMW paddles; 400 ft./min. chain speed; 12" canvas spout
Tractor Specs	Fits most late model tractors 90 HP or more (540 RPM PTO speed); Category III 3-point is standard; Category II requires special mounting pins On 40' standard scoops: (conveyor outside tire) the distance from the three-point to the lead edge of the front tire cannot exceed 175"; distance from the tractor PTO to the end of the axle (outside the tire) cannot exceed 55" On 35' center feed scoops: (conveyor inside tire) the distance from the centerline of the tractor to the centerline of the conveyor is 24"; conveyor is 14" wide
Undercarriage	Standard scoops only; castoring wheels; hydraulic lift; 3-point attachment to tractor; undercarriage supports conveyor when not on the tractor; 11L15 implement tires.

REACH AND ELEVATION

	Standard	Center Feed
Discharge Height*	11½' - 21½'	10' - 18½'
Discharge Reach*	19' - 14'	15' - 11'
Transport Height	13½'	13½'

*Lowest (16°) and highest (32°) inclines.

ACCESSORIES

- **Hydraulic spout:** Power rotation for the pan spout. This option also raises and lowers the spout.
- **Dump hopper:** For standard scoops only. Bolt-on panel forms a trough on the blade for unloading from trucks or wagons.



Standard scoop



Center feed scoop



Dump hopper, optional

**MADE
 IN THE
 USA**

*Learn more
 or get a quote*



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com