

GRAIN > PORTABLE AUGERS >
TD-450 AUGER

Load and unload bins with ease using the TD-450 Ox portable auger. Choose from multiple drive options, including electric, PTO, hydraulic, and gas engine. Available in tube diameters from 6 to 14 inches, it features a standard cage intake and optional 17° hopper.



Sudenga[®]
INDUSTRIES, INC.



- 6", 8", 10", 12" and 14" diameter tubes
 - Painted finish available in all sizes
- Galvanized tube finish available on sizes 6", 8", 10"
 - A-frame transport with manual winch
 - Hydraulic winch; 12" & 14" augers
 - PTO, electric, gas, and hydraulic drives

Learn more
or get a quote



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com

MADE
★IN THE★
USA

GRAIN > PORTABLE AUGERS > TD-450 AUGER



There's work to do. The Ox Top Drive Series is a beast. The TD-450 (Top Drive) Ox Portable Auger features multiple drive options including electric, PTO, hydraulic, and gas engine. Available in tube diameters of 6", 8", 10", 12" and 14". Standard cage intake, optional 17° hopper. Let it load and unload your grain bins. Let it fill or take away from your dryers. Just let it work. Available in painted or galvanized finishes.



SPECIFICATIONS

	6"	8"	10"	12"	14"
Tube Gauge	14 ga.		12 ga.		
Finish	Painted or galv.			Painted	
Flight Ga.; Tube ID	10 ga.; 1"	3/16"; 1½"	3/16"; 2½"	1/4"; 2⅞"	5/16"; 2⅞"
Driveshaft Diam.	1"		1¼"		
Head Chain	Single #50 (all lengths)	Single #60 (all lengths)	Single #80 (all lengths)	Single #80 (31'-41") Double #80 (51'-71")	Double #80 (31'-41") Belt drive (51'-86")
Gearbox** Shaft Diameter	1¼"			1¼" (31'-41") 1½" (51'-71")	1½"
Transport Arms	1⅞" round tube (26'-36'); 2" x 4" box upper & 2" x 3" box lower (41'-71")			2" x 4" box upper & 2" x 3" box lower (all lengths)	
Transport Width	7'8" (26'-41") 10' (51'-71")	7'8" (26'-41") 10' (51'-71")	7'8" (26'-41") 10' (51'-71")	7'8" (31'-41") 10' (51'-71")	7'8" (31'-41") 10'**** (51'-86")



Cage intake



Optional hopper

OPTIONS


- 17° or hinged hopper with removable hitch
- Swivel transport
- Wheeled jack
- Plastic hopper
- Hydraulic winch for 8" & 10" auger



Wheeled jack

* Intakes on all augers are double flighted.
** Gearbox is a right angle type, with miter cut gears and 1:1 ratio.
*** Axles extend to 13' for loading grain

REACH & ELEVATION



CAPACITIES

6" Augers	1,200 - 1,400 BPH
8" Augers	2,100 - 2,400 BPH
10" Augers	3,200 - 3,600 BPH
12" Augers	5,000 - 5,400 BPH
14" Augers	10,000 - 11,000 BPH

HOPPER DIMENSIONS 17° OR HINGED

Tube Dia.	Length	Width	Depth
8"	28"	27"	10"
10"	32½"	26½"	11¾"
12"	32½"	26½"	13"
14"	38½"	32"	15"

	Auger Length								
	26'	31'	36'	41'	51'	56'	61'	66'	71'
A - Elevation	16'	19'	23'	26'	31'	35'	38'	41'	44'
B - Reach	7'	10'	11'	14'	15'	18'	20'	21'	24'
C - Height	12'	13'	15'	16'	20'	21'	23'	25'	26'
D - Distance	14'	15'	17'	18'	25'	26'	28'	30'	31'



PTO drive



**MADE
★ IN THE ★
USA**

*Learn more
or get a quote*



1-888-SUDENGA | 1-712-475-3301 | Fax: 1-712-475-3320
PO Box 8, 2002 Kingbird Ave., George, IA 51237 USA
sales@sudenga.com | www.sudenga.com